

HIGH PRESSURE HAND PUMP

1,500 bar/21,750 psi



TWO STAGE, HIGH PRESSURE HAND PUMP

- Two-speed reduces handle strokes so you work faster and easier
- Built-in, protected pressure gauge
- Ergonomic design for minimal handle effort
- Lightweight aluminum reservoir
- Easily accessible refill port
- Needle valve allows full control when releasing tension

DESIGNED FOR

Electric



Air



Gas



Hand



MAINTENANCE
& REPAIR

ORIGINAL
INSTALL

Split



Tension



Torque



Max
Flow



Specifications and Dimensional Data

Size: (L x W x H): 62 cm x 11 cm x 17 cm
24.4" x 4.3" x 6.7"

Weight: 8.7 kg (19.1 lb) [with oil]

Maximum Oil Capacity: (vented reservoir)

1.1 L (0.29 Gallons) [to fill line]


1.0 L (0.26 Gallons) [usable]

Operating Environment: -25°C to +50°C
(-13°F to +122°F)

(When operating near temperature extremes, it is recommended to use hydraulic oils that are rated for those temperatures. Refer to service manuals and cooling options)

Pressure: 0 - 1,500 bar (0 - 21,750 psi)

Typical Flow: 20 cm³ stroke - 1 cm³ stroke
(1.22 in³/stroke - 0.061 in³/stroke)



Order No.	A mm in	B mm in	C mm in	D mm in	E mm in	F mm in	G1 mm in	G2 mm in	H mm in	J deg	K mm in	L mm in	M in
HPUHP150001	170	560	152	170	620	110	80	68	575	55	6.6	84	61/4"
	6.69	22	6	6.69	24.41	4.33	3.15	2.68	22.64	55	0.26	3.31	61/4"



Ordering Information

For use with	Order No	Speed	Volume per Stroke		Maximum Pressure		Handle Effort	Oil Capacity	Usable Oil Capacity	Oil Port	Product Weight
			LP in ³ cm ³	HP in ³ cm ³	LP psi bar	HP psi bar					
Tensioners	HPUHP150001	2	1.22	0.061	290	21750	83	61	61	61/4"	19.1
			20	1	20	1,500	370	1	1	61/4"	8.7